



RLE Technologies - Price List

(Effective April 1, 2014)

Product Code MSRP

SeaHawk Leak Detection Product Line

Spot Detectors - Conductive Fluids

Spot detector; conductive fluids, 14ft/4.26m leader, relay output, requires isolated 24VAC/VDC	SD-RO1	\$ 80.00
Spot detector; conductive fluids, 14ft/4.26m leader cable (for use with Falcon FMS products)	SD	\$ 57.00
Spot detector; conductive fluids, two 10in/0.25m male/female leader cables (for use with SeaHawk controllers)	SD-Z	\$ 115.00
Spot detector; conductive fluids, 14ft/4.26m leader cable (for use with SeaHawk zone controllers)	SD-Z1	\$ 50.00

Leak Detection Cable - Conductive Fluids (for use with SeaHawk controllers)

Sensing cable; conductive fluids, 10ft/3.04m, pre-installed male/female connectors	SC-10	\$ 146.00
Sensing cable; conductive fluids, 17ft/5.18m, pre-installed male/female connectors	SC-17	\$ 184.00
Sensing cable; conductive fluids, 25ft/7.62m, pre-installed male/female connectors	SC-25	\$ 216.00
Sensing cable; conductive fluids, 50ft/15.24m, pre-installed male/female connectors	SC-50	\$ 351.00
Sensing cable; conductive fluids, 100ft/30.48m, pre-installed male/female connectors	SC-100	\$ 594.00
Sensing cable; conductive fluids, custom length, pre-installed male/female connectors (Add a unique line for SC-B following this line item with the quantity being the total quantity in feet of SC required). Custom cables are non-returnable.	SC-CL	\$ 135.00
Sensing cable; conductive fluids, custom length, pre-installed EOL (Add a unique line item for SC-B following this line item with the quantity being the total quantity in feet of SC required). Custom cables are non-returnable.	SC-CL-EOL	\$ 135.00
Sensing cable; conductive fluids, custom length, pre-installed leader cable and EOL (Add unique line items for NSC-Band SC-B following this line item with the quantities being the total quantity in feet of NSC leader cable and SC required). Custom cables are non-returnable.	SC-CL-L-EOL	\$ 135.00
Sensing cable; conductive fluids, bulk footage, no connectors (may not be one continuous length of cable unless used as a SC-CL assembly)(Cable cut and spooling fee to be applied for lengths under 500')	SC-B	\$ 5.15 ft
Sensing cable - Purple; conductive fluids, bulk footage, 4.0 ohms/ft, no connectors (may not be one continuous length of cable unless used as a SC-CL assembly)(Cable cut and spooling fee to be applied for lengths under 500')	SC-P-B	\$ 5.90 ft

Leak Detection Cable - Acids/Chemicals (requires LC-KIT-M to integrate with SeaHawk controller)

Sensing cable; acids/chemicals, 3ft/0.91m, pre-installed male/female connectors	SC-C-3	\$ 263.00
Sensing cable; acids/chemicals, 10ft/3.04m, pre-installed male/female connectors	SC-C-10	\$ 314.00
Sensing cable; acids/chemicals, 17ft/5.18m, pre-installed male/female connectors	SC-C-17	\$ 361.00
Sensing cable; acids/chemicals, 25ft/7.62m, pre-installed male/female connectors	SC-C-25	\$ 418.00
Sensing cable; acids/chemicals, 50ft/15.24m, pre-installed male/female connectors	SC-C-50	\$ 616.00
Sensing cable; acids/chemicals, 100ft/30.48m, pre-installed male/female connectors	SC-C-100	\$ 976.00
Sensing cable; hydrocarbons & acids/chemicals, custom length, pre-installed male/female connectors (Add a unique line for SC-C-B following this line item with the quantity being the total quantity in feet of SC-C required). Custom cables are non-returnable.	SC-CL-M	\$ 257.00
Sensing cable; acids/chemicals, bulk footage, no connectors (may not be one continuous length of cable unless used as a SC-C-CL assembly, cable cut and spooling fee to be applied for lengths under 500')	SC-C-B	\$ 7.19 ft

Leak Detection Cable Controllers

Single zone leak detection controller; with audible, includes LC-KIT, requires WA-DC-5-ST (Replaces LD300)	LD310	\$ 210.00
Single zone leak detection controller; selectable audible, includes LC-KIT, requires PSWA-DC-24	LD1000	\$ 427.00
Six zone/input dual functionality controller; LC-KIT's not included, requires PSWA-DC-24	LDRA6	\$ 1,295.00
Distance-read leak detection module; includes LC-KIT, requires PSWA-DC-24	SeaHawk 10K	\$ 945.00
Distance-read leak detection integration controller; web enabled, includes LC-KIT, requires PSWA-DC-24	LD1500	\$ 859.00
Distance-read leak detection controller; LED display, web enabled, includes LC-KIT, requires PSWA-DC-24	LD2100	\$ 1,399.00
Distance-read leak detection controller; touch screen, web enabled, includes LC-KIT, requires 110/120/230-240VAC	LD5200	\$ 3,451.00

SNMP V3 Firmware Upgrades

LD5200 firmware; upgrade to support SNMPv3	5200-V3	\$ 319.00
LD2100 firmware; upgrade to support SNMPv3	2100-V3	\$ 319.00

Non-Sensing Cable

Non-sensing cable; 10ft/3.04m, pre-installed male/female connectors (for use with SC)	NSC-10	\$ 63.00
Non-sensing cable; 25ft/7.62m, pre-installed male/female connectors (for use with SC)	NSC-25	\$ 76.00
Non-sensing cable; 50ft/15.24m, pre-installed male/female connectors (for use with SC)	NSC-50	\$ 97.00
Non-sensing cable; 100ft/30.48m, pre-installed male/female connectors (for use with SC)	NSC-100	\$ 130.00
Non-sensing cable; custom length, pre-installed male/female connectors (for use with SC, add a unique line for NSC-B following this line item with the quantity being the total length of NSC required). Custom cables are non-returnable.	NSC-CL	\$ 135.00
Non-sensing cable; bulk, no connectors (for use with SC)(Cable cut and spooling fee to be applied for lengths under 500')	NSC-B	\$ 0.55 ft
Non-sensing cable; 10ft/3.04m, pre-installed male/female connectors (for use with SC-C)	NSC-10-M	\$ 173.00
Non-sensing cable; 25ft/7.62m, pre-installed male/female connectors (for use with SC-C)	NSC-25-M	\$ 203.00
Non-sensing cable; 50ft/15.24m, pre-installed male/female connectors (for use with SC-C)	NSC-50-M	\$ 255.00
Non-sensing cable; custom length, pre-installed male/female connectors (for use with SC-C, add a unique line for NSC-CH-B following this line item with the quantity being the total length of NSC required). Custom cables are non-returnable	NSC-CL-M	\$ 216.00

Product	Product Code	MSRP
Non-sensing cable; 100ft/30.48m, pre-installed male/female connectors (for use with SC-C)	NSC-100-M	\$ 359.00
Non-sensing cable; bulk, no connectors (for use with SC-C)(Cable cut and spooling fee to be applied for lengths under 500')	NSC-CH-B	\$ 2.05 ft
J-clips; qty 10 (for use with SC)	JC-10	\$ 13.00
J-clips; qty 25 (for use with SC)	JC-25	\$ 31.00
J-clips; qty 50 (for use with SC)	JC-50	\$ 54.00
J-clips; qty 200 (for use with SC)	JC-200	\$ 200.00
J-clips; qty 10 (for use with SC-C)	JC-C-10	\$ 16.75
J-clips; qty 25 (for use with SC-C)	JC-C-25	\$ 41.00
J-clips; qty 50 (for use with SC-C)	JC-C-50	\$ 77.00
J-clips; qty 200 (for use with SC-C)	JC-C-200	\$ 275.00

Leak Detection Accessories

Leader cable & end-of-line terminator; 15ft/4.57m (for SC integration into SeaHawk controllers)	LC-KIT	\$ 47.00 *
Leader cable & end-of-line terminator; 15ft/4.57m (for SC-C integration into SeaHawk controllers)	LC-KIT-M	\$ 88.00 *
Cable Caution Tags; qty 10	SC-T	\$ 10.15 *
Framed reference map; 11in x 14in (27.9cm x 35.5cm), includes electronic copy	FM1114	\$ 675.00 *
Weighted cable connector; simulates 50ft/15.24m of SC (for use with SC)	WCCS-50	\$ 28.00 *
Weighted cable connector; simulates 50ft/15.24m (for use with SC-C)	WCCS-50-M	Contact RLE
X-Connector; single input, three "branch" outputs, simulates 150ft/45.72m (for use with SC)	X-CON	\$ 149.00 *
X-Connector; single input, three "branch" outputs, simulates 150ft/45.72m for use with SC-C)	X-CON-M	Contact RLE
End-of-line terminator (for use with SC)	EOL	\$ 20.00 *
End-of-line terminator (for use with SC-C)	EOL-M	\$ 41.00 *
Male/Male & Female/Female adapter kit (for use with SC)	SCC-KIT	\$ 68.00 *
Wall mount enclosure; requires 110/120/230-240VAC (for use with LD1500 & LD2100)	LD-ENC	\$ 338.00 *
Wall mount enclosure (for use with LD1500 & LD2100)	LD-ENC-NP	\$ 182.00 *
Rack mount bracket for LD2100, 19in/482mm	LD2100-RMB	\$ 49.00 *

Cable Connectors Construction

Cable connector kit; includes parts for male/female connector installation (for use with SC/NSC)	CCK-LD	\$ 54.00 *
Contact extractor (for use with CCK-LD, tools are non-returnable)	CPCE	\$ 45.00 *
Cable pin crimp tool (for use with CCK-LD, tools are non-returnable)	SCPC	\$ 385.00 *
Cable stripper (for use with CCK-LD, tools are non-returnable)	SCCS	\$ 220.00 *

Cable Tester

Cable evaluator; multi-meter not included (for use with SC)	LDCE	\$ 120.00 *
---	------	-------------

Falcon Alarm Monitoring and Notification Product Line

1RU: 1 Rack Unit, 2U: 2 Rack Unit, UI: Universal Input, AI: Analog Input, DI: Digital Input (Dry Contact), RO: Relay Output

Monitoring appliance; 8 DI, 4 RJ-11 inputs, 1 - single zone leak detection input, 1 relay output, network cable, standard USB-A to mini-B cable, and (US) 5VDC USB power adapter w/ 12V boost	F200	\$ 595.00
<i>All FMS products accommodate: 8 UI (dry contact / 4-20mA), 2 RO, SNMP and Modbus</i>		
Monitoring appliance; 1RU, 1 expansion card slot, includes (US) 100-240VAC to 24VDC wall adapter	FMS-x-n-24	\$ 2,457.00
Monitoring appliance; 1RU, 1 expansion card slot, internal temp/humidity sensor, includes (US) 100-240VAC to 24VDC wall adapter	FMS-x-Y-24	\$ 2,565.00
Monitoring appliance; 1RU, 1 expansion card slot, requires 48VDC	FMS-x-n-48	\$ 2,781.00
Monitoring appliance; 1RU, 1 expansion card slot, internal temp/humidity sensor, requires 48VDC	FMS-x-Y-48	\$ 2,889.00
Monitoring appliance; 2RU, 4 expansion card slots, includes 85-264VAC to 24VDC desktop adapter with (US) cord	FMS-xxxx-n-24	\$ 2,587.00
Monitoring appliance; 2RU, 4 expansion card slots, internal temp/humidity sensor, includes 85-264VAC to 24VDC desktop adapter with (US) cord	FMS-xxxx-Y-24	\$ 2,695.00
Monitoring appliance; 2RU, 4 expansion card slots, requires 48VDC	FMS-xxxx-n-48	\$ 3,013.00
Monitoring appliance; 2RU, 4 expansion card slots, internal temp/humidity sensor, requires 48VDC	FMS-xxxx-Y-48	\$ 3,121.00

Wireless Gateways

Wireless Gateway; 418/900 MHz receiver, 4 digital inputs / 2 relay outputs, includes (US) 100-240VAC to 24VDC power adapter	Wi-MGR	\$ 1,595.00
Wireless Gateway; 433MHz/2.4GHz receiver, includes (US) 100-240VAC to 24VDC power adapter	FDS-Wi-EU	Contact RLE

FMS Expansion Options

FMS Expansion Card; 12 UI (N/O dry contact, 4-20mA, 0-5 VDC, 0-10VDC) and 8 RO, limit one per 48VDC FMS (for use with 24VDC or 48VDC FMS models)	EXP-A-24/48	\$ 967.00
FMS Expansion Card; 24 DI (24VDC FMS models only)	EXP-C-24	\$ 643.00
FMS Expansion Card; 24 DI (48VDC FMS models only)	EXP-C-48	\$ 697.00
Internal Modem (for use with FMS)	EXP-IM	\$ 385.00
FMS firmware; upgrade to support SNMPv3	FMS-V3	\$ 319.00

Falcon Installation Accessories

Wall mount brackets (for use with, FMS & FDS-Wi, Wi-MGR and Protocol Converter)	WMB	\$ 43.00
Rack mount brackets; 19in/482mm, qty 2 (for use with F200)	F200-RMB	\$ 57.00 *
Wire harness; 15ft/4.57m tinned wires (for use with FMS main board I/O)	EM-WHMB-T	\$ 292.00
Wire harness; 15ft/4.57m tinned wires (for use with FMS expansion cards I/O)	EM-WHEC-T	\$ 297.00

Raptor Integration Solution Product Line

Protocol Converters

Protocol Converter; SNMP/Modbus/BACnet, includes (US) 100-240VAC to 24VDC power adapter	FDS-PC	\$ 995.00
Protocol Converter; SNMP/Modbus/BACnet, dual port RS485, includes (US) 100-240VAC to 24VDC power adapter	FDS-PC-DP	\$ 1,375.00

Alarm Status Panels

Single input alarm status panel / relay replicator; one input and two outputs, requires 24VAC/VDC	RA1x2	\$ 205.00
---	-------	-----------

Product	Product Code	MSRP
Six zone/input dual functionality controller; requires 24VAC/VDC	LDRA6	\$ 1,295.00
Relay Replicators		
Single input alarm status panel / relay replicator; one input and two outputs, requires 24VAC/VDC	RA1x2	\$ 205.00
Relay replicator; 10 inputs and 20 outputs, requires 24VAC/VDC	RR10X20	\$ 702.00
Relay replicator; 10 inputs and 20 outputs, requires 48VDC	RR10X20-48	\$ 713.00
Relay replicator; 20 inputs and 40 outputs, requires 110/120/230-240VAC	RR20X40	\$ 1,674.00
Sensors & Accessories		
Temperature & Temperature/Humidity Sensors		
F110/F200 temperature sensor; 25ft/7.62m with RJ-11 connector	F110-TS	\$ 52.00 *
F110/F200 temperature/humidity sensor; 25ft/7.62m with RJ-11 connector	F110-THS	\$ 113.00 *
Temperature sensor; 10K thermistor	T10K	\$ 12.50 *
Temperature sensor; 4-20mA, wall mount, 12-24VDC	TEAMS	\$ 83.00 *
Temperature sensor with LCD display; 4-20mA, wall mount, requires 12-24VDC	T120D	\$ 106.00 *
Temperature sensor probe, Range: 40F to 100F, 4-20mA loop powered, 18in/45cm leader	TSP-18IN	\$ 93.00 *
Temperature sensor probe; Range: 40F to 100F, 4-20mA loop powered, 5ft/1.52m leader	TSP-5FT	\$ 94.00 *
Temperature sensor probe; Range: 40F to 100F, 4-20mA loop powered, 25ft/7.62m leader	TSP-25FT	\$ 99.00 *
Temperature sensor; wide range: 4-20mA transmitter & probe (please specify the desired range)	T400	\$ 223.00 *
Temperature sensor; pipe strap on, 4-20mA, requires 12-24VDC	TSO	\$ 135.00 *
Temperature sensor; duct mount, 4-20mA, requires 12-24VDC	DMTS	\$ 161.00 *
Temperature sensor; outdoor, -40F to 122F, 4-20mA, requires 12-24VDC	T120-O	\$ 134.00 *
Temperature / Humidity sensor; 4-20mA, wall mount, requires 12-24VDC	TH140	\$ 266.00 *
Temperature/Humidity sensor with LCD display; 4-20mA, wall mount, requires 12-24VDC	TH140D	\$ 301.00 *
Temperature/Humidity sensor; outdoor, -40F to 122F, 4-20mA, requires 12-24VDC	TH140-O	\$ 401.00 *
Humidity sensor; wall mount, 4-20mA, requires 12-24VDC	H130	\$ 231.00 *
Wireless Repeaters, 418 & 433 MHz Wireless Point Sensors/Transmitters and Accessories		
Wireless Repeater (Mesh repeater); 418 MHz receiver with 900 MHz transmitter, includes (US) 120VAC to 9VDC power adapter	Wi-PR	\$ 425.00 *
Wireless Repeater (Mesh repeater); 433 MHz receiver with 2.4GHz transmitter, includes 100-240VAC to 9VDC power adapter with type "C" and "G" blades	Wi-PR-EU	\$ 523.00 *
Wireless field tester for 418/900 MHz applications	Wi-FT	\$ 2,369.00
Temperature sensor; 418 MHz wireless transmitter	Wi-TS	\$ 109.00 *
Temperature sensor; 418MHz wireless transmitter, 10K-2 thermistor	Wi-TS-S1	\$ 220.00 *
Temperature sensor; 418MHz wireless transmitter, external 1.75in/44mm SS remote probe w/ 10K-2 thermistor	Wi-TS-S2	\$ 240.00 *
Temperature sensor; 418MHz wireless transmitter, external 2in/50mm hanging thermobuffer w/ 10K-2 thermistor	Wi-TS-S3	\$ 310.00 *
Temperature sensor; 433 MHz wireless transmitter	Wi-TS-433	\$ 136.00 *
Temperature and counter/dry contact sensor; 418 MHz wireless transmitter	Wi-DIT	\$ 175.00 *
Temperature and humidity sensor; 418 MHz wireless transmitter - 2.7"W x 4.4"H x 1.1"D (69mmx112mmx28mm)	Wi-THS-B	\$ 181.00 *
Temperature and humidity sensor; 418 MHz wireless transmitter	Wi-TH2	\$ 190.00 *
Temperature and humidity sensor; 433 MHz wireless transmitter	Wi-THS-433	\$ 226.00 *
Leak detector w/ spot detector; 418MHz wireless transmitter, includes 14ft/4.26m leader	Wi-LD-SPOT	\$ 263.00 *
Leak detector for sensing cable; 418MHz wireless transmitter, includes LC-Kit, requires sensing cable (50ft/15.24m maximum)	Wi-LD	\$ 275.00 *
Analog input (0-20mA); 418 MHz wireless transmitter	Wi-AS420	\$ 211.00 *
Analog input (0-5v); 418 MHz wireless transmitter	Wi-AS5	\$ 211.00 *
Analog input (0-10v); 418 MHz wireless transmitter	Wi-AS10	\$ 211.00 *
3.6V Lithium battery for Wireless Sensors	Wi-BAT	\$ 6.85 *
900 MHz Wireless Point Sensors/Transmitters		
Temperature sensor; 900 MHz wireless transmitter	Wi-TS9	Contact RLE
Temperature and humidity sensor; 900 MHz wireless transmitter	Wi-THS9	Contact RLE
Outdoor antenna; 900 MHz	Wi-ANT9	\$ 26.25 *
Power Monitors (Additional power monitoring sensors are available. Contact RLE with your specific needs)		
Power fail monitor for (US) 120VAC power receptical, type "B" blades (with ground), relay output	PFM	\$ 145.00
Power fail monitor, 230VAC, relay output	PFM-I	\$ 196.00
Ground fault monitor; dual relay outputs, requires 120/203-240VAC	GFM600-2	\$ 2,695.00
Single Phase Current Sensors		
Current sensor; 0.15 - 200 Amps, trip point .015A or less, N.O. relay output	CT015	\$ 50.00 *
Current sensor; 0-120 Amps, 4-20 mA, split core	CT120	\$ 93.00 *
Current sensor; 100-300 Amps, 4-20 mA, split core	CT300	\$ 200.00 *
Current sensor; 0-400 Amps, split core, Voltage output	CT400	\$ 171.00 *
Current sensor; 300-800 Amps, 4-20 mA, split core	CT800	\$ 238.00 *
Current sensor; 1000-2400 Amps, 4-20 mA, split core	CT2400	\$ 379.00 *
Power Meters - 3-Phase		
Power meter; 3-phase, 100A max., Modbus, small	PM100	\$ 1,014.00 *
Power meter; 3-phase, 300A max., Modbus, small	PM300	\$ 1,044.00 *
Power meter; 3-phase, 400A max., Modbus, medium	PM400	\$ 1,075.00 *
Power meter; 3-phase, 800A max., Modbus, medium	PM800	\$ 1,105.00 *
Power meter; 3-phase, 800A max., Modbus, large	PM800L	\$ 1,135.00 *
Power meter; 3-phase, 1600A max., Modbus, large	PM1600	\$ 1,167.00 *
Power meter; 3-phase, 2400A max., Modbus, large	PM2400	\$ 1,196.00 *
Branch Circuit Monitors		
BCM; 12 circuits, 3/4" centers, Modbus, split core	BCM-12-SP	\$ 1,840.00 *
BCM; 24 circuits, 3/4" centers, Modbus, split core	BCM-24-SP	\$ 1,893.00 *

Product	Product Code	MSRP
BCM; 30 circuits, 3/4" centers, Modbus, split core	BCM-30-SP	\$ 2,169.00 *
BCM; 42 circuits, 3/4" centers, Modbus, split core	BCM-SP	\$ 2,744.00 *

Branch Circuit Monitors - Electrical Load Management

BCM; 42 circuits, includes split core 50A CT's, Modbus (energy consumption, KWH) requires 90-277 VAC	EBCM-42-SP	\$ 4,839.00 *
BCM; 84 circuits, includes split core 50A CT's, Modbus (energy consumption, KWH) requires 90-277 VAC	EBCM-84-SP	\$ 7,331.00 *
BCM; 42 circuits, requires CT's and two ribbon cables, Modbus (energy consumption, KWH) requires 90-277 VAC	EBCM-42	\$ 3,570.00 *
BCM; 84 circuits, requires CT's and four ribbon cables, Modbus (energy consumption, KWH) requires 90-277 VAC	EBCM-84	\$ 4,676.00 *

EBCM-42/84 components:

Ribbon cable for EBCM-42 and EBCM-84	EBCM-RC	\$ 38.00 *
50A CT six pack for EBCM-42 and EBCM-84, 6ft (1.8m) leads	EBCM-50A	\$ 215.00 *
100A CT six pack for EBCM-42 and EBCM-84, 4ft (1.2m) leads	EBCM-100A	\$ 471.00 *

Fire & Security - RLE PRODUCTS ARE NOT CERTIFIED FOR "LIFE SAFETY" APPLICATIONS

Motion sensor; requires 12-24VDC	MD3	\$ 31.00 *
Magnetic door sensor	MDS	\$ 17.50 *
Smoke detector; photoelectric, requires 12-24VDC	SMK	\$ 66.00 *

Gas Sensors

Gas detector; hydrogen default, can be field calibrated to detect: Methane, Butane, Ethanol, Propane or general LEL (most any combustible gas) two relays, adjustable setpoints, 4-20mA output, requires 24VAC/VDC	GD100	\$ 494.00 *
Replacement sensor for GD100 gas detector	GD100-RS	\$ 106.00 *

Power Supplies & Adapters

Wall Adapters (USA)

Power adapter; 120VAC to 24VAC, (US) type "A" blades, stripped end (for use with the SD-RO1)	WA-AC-24-ST	\$ 21.00 *
Power adapter; 100-240V to 5VDC, (US) type "A" blades, stripped end (for use with the LD300)	WA-DC-5-ST	\$ 18.75 *
Power adapter; 100-240VAC to 24VDC, w/ barrel connector, includes (US) type "A" blades	PSWA-DC-24	\$ 40.00 *

International Blades for the PSWA-DC-24

EU blade (type "C") for the PSWA-DC-24	Blade-EU	\$ 3.75 *
UK blade (type "G") for the PSWA-DC-24	Blade-UK	\$ 6.25 *
AU blade (type "I") for the PSWA-DC-24	Blade-AU	\$ 5.00 *

Desktop Adapters- 85-264VAC - 50/60HZ to 24VDC

Power adapter; 85-264VAC, barrel connector on 24VDC side, power cord not included	PSDT	\$ 51.00 *
Power adapter; 85-264VAC, barrel connector on 24VDC side, includes (US) power cord	PSDT KIT	\$ 61.00 *

Power Cords for PSDT Adapters

Power cord; EU (type "C")	DTPC-2	\$ 15.00 *
Power cord; EU (type "C"), right angle	DTPC-3	\$ 13.75 *
Power cord; UK (type "G") w/ fuse	DTPC-4	\$ 21.25 *

J-Box

Power adapter in J-box; 120VAC to 24VDC	JBX	\$ 88.00 *
Power adapter in J-box; 48VDC to 24VDC	JBX-48	Contact RLE

Extended Warranty

RLE offers a one-year standard warranty on all products. Please contact RLE for warranty return details.

Extended Warranty, additional 2 years	EW2 - 20% of purchase price
Extended Warranty, additional 3 years	EW3 - 40% of purchase price
Extended Warranty, additional 4 years	EW4 - 60% of purchase price

Start-Up & Commissioning

a formal quote, and/or to schedule start-up services. All panel mounting, field point to point wiring and power wiring is to be completed by others.

Product Service & Repairs

Please contact RLE for details regarding our product service and repair policies.

Comments and Notes

* Items priced at a non-standard price - Standard discount multipliers do not apply.

- All prices US\$, C.P.T. factory - Fort Collins, CO USA per Incoterms 2010. Any associated shipping/bank charges are not included.
- Prices are subject to change at any time without notice.

RLE Technologies
104 Racquette Dr.
Fort Collins, CO 80524
www.RLETech.com
970.484.6510
Sales@RLETech.com